

# 1- sliding door underbench safety cabinet Type 30

## COMPLIANCE

EN 14470-1

## ADVANTAGES

- 30-minute fire resistant and made in France
- EN 14470-1 and FM 6050 compliant
- Storage of flammables, corrosives and toxics

## BUT ALSO...

- Thermo-expanding seals of the doors
- Adjustable leveling feet for enhance stability
- Locking system
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Tested and approved according to FM 6050



## TECHNICAL FEATURES

Model	<b>7032T</b>	Door closure	<b>manual closing</b>
Compliance	<b>EN 14470-1</b>	Shipping dimensions HxWxD (mm)	<b>835 x 1200 x 800</b>
Cabinet materials	<b>Melamine wood structure</b>	Ventilation	<b>Both inlet and outlet on the back wall of the cabinet</b>
Doors color	<b>light grey RAL 7035</b>	Openings diameter (mm)	<b>100</b>
Number of doors	<b>1</b>	Number of compartments	<b>1</b>
Doors type	<b>sliding doors</b>	HS Code	<b>94036000</b>

## ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Connecting kit (Réf : KRC)
- Vertical recycling air box (delivered without filter) (Réf : H40+)

## OPTIONS

- Perforated cover plate for cabinets 762T - 792T (Réf : C2T)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
7032T	635 x 1115 x 630	310 x 1000 x 475	60		0	50	108.00