791+ARD

1- door underbench safety cabinet Type 90 - with waste recovery

COMPLIANCE

EN 14470-1, EN 1363-1

ADVANTAGES

- EN 14470-1 Type 90 compliant
- EN 14470-1 and EN 1363-1 compliant
- Storage of flammables

BUT ALSO...

- Thermo-expanding seals of the doors
- Locking system
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Fixation for earthing
- 90-minute fire resistant according to EN 14470-1, and tested until 105 minute
- Tested and approved according to FM 6050
- Tested and approved with ISO 834 fire heating curve by an European laboratory
- Complete system for recovery of waste provided

TECHNICAL FEATURES

Model	**791+ARD**	Door closure	**self-closing**
Compliance	**EN 14470-1, EN 1363-1**	Shipping dimensions HxWxD (mm)	**900 x 1200 x 800**
Cabinet materials	**12/10th epoxy painted steel structure**	Ventilation	**Both inlet and outlet on the back wall of the cabinet**
Doors color	**white RAL 9010**	Openings diameter (mm)	**100**
Number of doors	**1**	Number of compartments	**1**
Doors type	**swing doors**	HS Code	**94032080**
Hinges	**right**		

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic vapors (Réf : CDF-A)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Connecting kit (Réf : KRC)
- Vertical recycling air box (delivered without filter) (Réf : H40+)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
791+ARD	630 x 635 x 570	420 x 490 x 285	30		0	0	160.00

TRIONYX
1er FABRICANT FRANCAIS
Armoires de sécurité pour produits dangereux

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr