



Safety eye-washer for indoor out outdoor use

COMPLIANCE

EN 15154-2

ADVANTAGES

- ISO 3864 compliant
- EN 15154-2 compliant
- First-aid in case of chemical projection

BUT ALSO...

- Anti-dust caps for dusty environment
- Compliant to the article R. 4224-14 of the Labour Code
- Allows to rinse itself the eyes in case of chemical projection
- Delivered with the first-aid labelling
- EN 15154-2 compliant



TECHNICAL FEATURES

Model	LP24	Bowl	inox + epoxy painted RAL 6032
Compliance	EN 15154-2	Pipe	galvanised steel + grey epoxy painted RAL 7040
Shipping dimensions HxWxD (mm)	340 x 320 x 720	Water inlet	F1"
Use	internal use & external use	Water outlet	F1 1 / 4"
Setting	handle and foot operating	HS Code	73242921
	mounted on feet		

COMPLEMENTARY PRODUCTS

- Heating cable kit (Réf : KITCC2)

OPTIONS

- Thermostatic mixing valve for safety eye-wash (Réf : MCL)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Eye-washer flow (L/min)	Shower flow (L/min)	Weight (kg)
LP24	H1040		15	0	8.00